

TEST REPORT

Report Ref. No. 13EMC-RT-0874

Date of issue 2013-07-16

Applicant

- Name Samsung Techwin Co., Ltd.
- Address #42 Seongju-Dong, Changwon-Shi, Kyungsangnam-Do, Korea

Factory

- Name TIANJIN SAMSUNG TECHWIN OPTO-ELECTRONIC CO., LTD
- Address No.11 Weiliu Road. Micro-Electronic Industrial Park Jingang Road Tianjin 300385, China

Equipment

- Product Network Camera
- Model SNV-6084R* (* is N or P, N:NTSC/ P:PAL)

Standard IEC 62262 and IEC 60068-2-75

Technician Hyunwook, Song



Approved Jaekyu, Lee



1. Reference Documents

IEC 62262 and IEC 60068-2-75

Degrees of protection provided by enclosure for electrical equipment against external mechanical impacts (IK code)

2. Test Performed

Degree of protection provided by enclosure for external impacts IK10++

3. General Test Conditions

tamb: 25 °C

RH: 54 %

4. Test Conditions

According to standard IEC 62262 and IEC 60068-2-75

The verification of IK10++ has been done positioning the enclosure on a rigid support.

5 impacts have been applied on each surface in sight with the enclosure.

For the test used Pendulum Hammer

IK10++ (Characteristics of impact test):

Energy: 50 Joule

Mass: 10 kg

High Δ h: 500 mm

5. Drop Zones:

The areas that were focused upon for this impact test are as follows:



6. Test Results

Drop Zone: Enclosure		
Drop #	Orientation / Results	Pass / Fail
Drop 1	Normal to surface of enclosure. Scuff	Pass
Drop 2	Normal to surface of enclosure, about 90° circumferentially from previous drop. Scuff	Pass
Drop 3	Normal to surface of enclosure, about 90° circumferentially from previous drop. Side cover open (7.8 mm)	Pass
Drop 4	Normal to surface of enclosure, about 90° circumferentially from previous drop. Scuff	Pass
Drop 5	Normal to surface of enclosure, about 90° circumferentially from previous drop. Scuff	Pass

Drop Zone: Window		
Drop #	Orientation / Results	Pass / Fail
Drop 1	Vertical drop onto center of Window. Scuff	Pass
Drop 2	Normal to surface of side Window. Scuff	Pass
Drop 3	Normal to surface of side Window, about 90° circumferentially from previous drop. Scuff	Pass
Drop 4	Normal to surface of side Window, about 90° circumferentially from previous drop. Scuff	Pass
Drop 5	Normal to surface of side Window, about 90° circumferentially from previous drop. Scuff	Pass

7. Images





Conclusion

After testing according to the procedure set forth by IEC 62262, SNV-6084R* was found to meet the criteria required for an IK10++ specification.