



Samsung is a leading supplier of advanced video surveillance solutions for IP-video, analog and hybrid systems. Building on the company's history of innovation, Samsung Security Systems is dedicated to providing systems solutions with the highest levels of performance, reliability and cost-efficiency. Samsung is committed to the continued development of innovative systems products for professional security applications.

For additional information, contact:

Samsung Security
100 Challenger Road
Suite 700
Ridgefield Park, NJ USA
Phone: +1 877 213-1222
Web: www.samsung-security.com
E-mail: info@samsungsecurity.com

1.3 MP HD 23x NETWORK PTZ DOME CAMERA

DIVISION 28 – ELECTRONIC SAFETY AND SECURITY

Notes to Specifier:

1. Where several alternative parameters or specifications exist, or where, the specifier has the option of inserting text, such choices are presented in **<bold text>**.
2. Explanatory notes and comments are presented in **colored** text.

Important: See further notes on the following page.

Important Note to Security Systems Specifiers

CSI MasterFormat 2016 incorporates numerous significant changes affecting electronic safety and security. This document is written to provide flexibility in using either format, although adoption of MasterFormat 2016 is encouraged. The following is a guide to the MasterFormat numbers relevant to the product referenced in this specification.

Primary Specification Area:**MasterFormat 2014:**

28 20 00	Electronic Surveillance
28 23 00	Video Surveillance
28 23 29	Video Surveillance Remote Devices and Sensors

MasterFormat 2016:

28 20 00	Video Surveillance
28 2x xx	Surveillance Cameras
28 2x xx	IP Cameras

Related Requirements:**MasterFormat 2014:**

27 20 00	Data Communications
28 23 13	Video Surveillance Control and Management Systems
28 23 16	Video Surveillance Monitoring and Supervisory Interfaces
28 23 19	Digital Video Recorders and Analog Recording Devices
28 23 23	Video Surveillance Systems Infrastructure

MasterFormat 2016

27 15 01.xx	Video Surveillance Communications Conductors and Cables
27 20 00	Data Communications
28 05 xx.xx	PoE Power Sources for Electronic Safety and Security
28 05 xx	Storage Appliances for Electronic Safety and Security
28 05 xx.xx	Network Video Recorders
28 05 xx	Cyber Requirements for Electronic Safety and Security
28 05 xx	Safety and Security Network Communications Equipment
28 2x 00	Video Management System

1.3 MP HD 23x NETWORK PTZ DOME CAMERA

PART 1 GENERAL

1.01 SUMMARY

- A. Section includes a 1.3 MP IP video camera in dome housing with PTZ capability.
- B. Product - A 1.3 MP IP video camera, with multi-streaming (H.264 and MJPEG) capability and 23x zoom ratio in dome housing.
- C. Related Requirements

Refer to MasterFormat notes at the beginning of this document to select requirements specific to the MasterFormat version being used in the specification.

1.02 REFERENCES

- A. Abbreviations
 - 1. AGC - Automatic Gain Control
 - 2. ARP – Address Resolution Protocol
 - 3. AWB - Automatic White Balance
 - 4. BLC – Back light compression
 - 5. CBR – Constant Bit Rate
 - 6. CVBS – Color, Video, Blanking, Sync
 - 7. DHCP - Dynamic Host Configuration Protocol
 - 8. DNR – Digital Noise Reduction
 - 9. DNS - Domain Name Server
 - 10. DDNS – Dynamic Domain Name Server
 - 11. DSCP – Differentiated Services Code Point
 - 12. fps - frames per second
 - 13. FTP - File Transfer Protocol
 - 14. GOV – Group of Video
 - 15. GUI – Graphical User Interface
 - 16. HD – High Definition
 - 17. HTTP - Hypertext Transfer Protocol
 - 18. ICMP – Internet Control Message Protocol
 - 19. IGMP - Internet Group Management Protocol
 - 20. IP - Internet Protocol
 - 21. JPEG - Joint Photographic Experts Group
 - 22. MJPEG - Motion JPEG
 - 23. MP - Megapixel
 - 24. MPEG - Moving Pictures Experts Group

25. NAS – Network Attached Storage
26. NTP - Network Time Protocol
27. PIM-SM - Protocol Independent Multicast-Sparse Mode
28. PoE - Power over Ethernet
29. PPPoE – Point to Point Protocol over Ethernet
30. RTP - Real-Time Transport Protocol
31. RTCP – Real-Time Control Protocol
32. RTSP - Real-Time Streaming Protocol
33. SDK – Software Development Kit
34. SMTP - Simple Mail Transfer Protocol
35. SNMP – Simple Network Management Protocol
36. SSL – Secure Sockets Layer
37. TCP - Transmission Control Protocol
38. UDP - User Datagram Protocol
39. UPnP – Universal Plug and Play
40. VBR – Variable Bit Rate
41. VMS - Video Management System
42. WDR – Wide Dynamic Range

B. Reference Standards

1. Network - IEEE
 - a. 802.3 Ethernet Standards
 - b. 802.1x Port-based Network Access Control
2. Video
 - a. ISO / IEC 14496–10, MPEG-4 Part 10 (ITU H.264)
 - b. ISO / IEC 10918 – JPEG
 - c. ONVIF – Profiles S
3. Emissions
 - a. FCC-47 CFR Part 15 Subpart B Class B
 - b. CE EN 55022:2010
4. Immunity - CE
 - a. EN 50130-4:2011
 - b. EN 61000-3-3:2014
 - c. EN 61000-4-2:2009
 - d. EN 61000-4-3:2006+A2:2010
 - e. EN 61000-4-4:2012
 - f. EN 61000-4-5:2014
 - g. EN 61000-4-6:2009
5. Safety
 - a. UL listed
 - b. CE EN 50581:2012 (hazardous substances)

6. Ingress Protection and Vandal Resistance

- a. IEC EN 62262 - Degrees of protection provided by enclosures for electrical equipment against external mechanical impacts – IK10 (with SHP-3701H)

C. Definitions

- 1. GOV (Group of Video object planes) - A set of video frames for H.264 compression, indicating a collection of frames from the initial I-Frame (key frame) to the next I-Frame. GOV consists of 2 kinds of frames: I-Frame and P-Frame.
- 2. Multi-exposure wide dynamic range - Operation which automatically adjusts shutter speed to provide a wide range between dark and light areas visible at the same time, preventing backlighting issues. Long exposure is used for bright areas and a short exposure is used in dark areas.
- 3. Smart Codec – Operation in which the camera adaptively alters the video compression for a portion of the camera's field of view to improve the quality of video in the area specified.

1.03 SUBMITTALS

A. Product Data

- 1. Manufacturer's printed or electronic data sheets
- 2. Manufacturer's installation and operation manuals
- 3. Warranty documentation

1.04 QUALIFICATIONS

- A. Manufacturer shall have a minimum of five years' experience in producing IP video equipment.
- B. Installers shall be trained and authorized by the Manufacturer to install, integrate, test, and commission the system.

1.05 DELIVERY, STORAGE AND HANDLING

- A. Deliver the camera in the manufacturer's original, unopened, undamaged container with identification labels intact.
- B. Store the camera in a temperature environment of -30° C to 60° C (-22° F to 140° F), protected from mechanical and environmental conditions as designated by the manufacturer.

1.06 WARRANTY, LICENSING AND SUPPORT

- A. Manufacturer shall provide a limited 3 year warranty for the product to be free of defects in material and workmanship.
- B. Manufacturer shall provide embedded camera video analytics free of license charges.

END OF SECTION

PART 2 PRODUCTS

2.01 EQUIPMENT

- A. Manufacturer: Samsung Security
 100 Challenger Road
 Suite 700
 Ridgefield Park, NJ USA
 Phone: +1 877 213-1222
 Web: www.samsung-security.com
 E-mail: info@samsungsecurity.com
- B. Model SNP-L5233H
- C. Alternates: None

2.02 GENERAL DESCRIPTION

- A. Video Compression and Transmission – The 1.3 MP camera shall have the following properties relating to the video signals it produces.
1. H.264 and MJPEG compression, each derived from a dedicated encoder and capable of being streamed independently and simultaneously
 - a. H.264 – frame rates up to 30 fps
 - b. MJPEG – frame rates up to 30 fps

Maximum frame rates are available at selected resolutions:

H.264: 30 fps is available at all resolutions

MJPEG: 30 fps available up to and including 800 x 600 resolution: 15 fps at all higher resolutions

2. The 1.3 MP camera shall be able to configure up to 10 independent video stream profiles with differing encoding, quality, frame rate, resolution, and bit rate settings.
 3. Resolution selections
 - a. 720p (1280 x 720) HD
 - b. 1280 x 1024, 1280 x 960, 1280 x 720, 1024 x 768, 800 x 600, 800 x 450, 720 x 576, 640 x 480, 640 x 360, 320 x 240, 320 x 180
 4. Simultaneous unicast access by up to 10 users
 5. Multicast or unicast capable
 6. Dynamic DNS (DDNS) support
 7. 1V peak-peak composite video output signal at camera for setup and diagnostics
- B. Camera – The 1.3 MP camera device shall have the following physical and performance properties:
1. Dustproof, waterproof, and IP66 rated.
 2. True day/night operation with removable IR cut filter
 - a. Low light level operation to 0.15 lux (color) and 0.015 lux (black and white)
 3. 100 dB multi-exposure Wide Dynamic Range, providing a wide range between dark and light areas visible at the same time

4. 2D and 3D digital noise reduction
 5. Digital zoom
 6. 32 privacy masking regions utilizing a 4 point polygon
 7. Digital image stabilization
- C. Intelligence and Analytics – The 2 MP camera shall have a suite of integral intelligent operations and analytic functions to include:
1. Motion detection with four definable detection areas, minimum / maximum object size definition and a learning algorithm that ignores false alarms such as trees and waves on water.
 2. Detection of logical events of specified conditions from the camera's video input
 - a. line crossing (passing)
 - b. appear/disappear
 - c. audio detection
 - d. camera tamper (scene change)
 - e. enter/exit a predefined zone
 3. Face detection used to create an event whenever there is a face or multiple faces in the image, up to detection of 32 faces simultaneously
 4. Audio detection above a specified threshold
 5. Smart Codec operation in which the camera adaptively alters the video compression for a region of interest or a detected face to improve the quality of video in the area specified.
 - a. definable up to 5 regions of interest
- D. Interoperability – The 1.3 MP camera shall be ONVIF Profile S compliant.
- E. The 1.3 MP camera shall possess the following further characteristics:
1. Built-in web server, accessed via standard browsers including Internet Explorer, Firefox, Chrome & Safari
 2. Micro SD/SDHC/SDXC memory card and NAS recording options, with configurable pre-alarm and post-alarm recording intervals
 3. Bi-directional audio
 4. Alarms and notifications
 - a. 4 physical alarm input and 2 output
 - b. alarm notification triggers:
 - 1.) video analytics
 - 2.) motion detection
 - 3.) tampering
 - 4.) audio detection
 - 5.) face detection
 - 6.) network disconnection
 - 7.) physical alarm input
 - 8.) event from embedded third party application
 - c. available notification means upon trigger:
 - 1.) file upload via FTP and e-mail
 - 2.) notification via e-mail
 - 3.) record to local storage (SD card)

- 4.) record to network storage
- 5.) external output
- 5. POE capable

2.03 CAMERA SOFTWARE

- A. The 1.3 MP camera shall have a built in web server which supports browser-based configuration using Internet Explorer, Google Chrome, Mozilla Firefox, and Apple Safari, for which web viewer plug-ins are available, from a PC or Mac.
- B. The web viewer shall provide a monitoring screen which displays live camera video and simultaneously provides same-screen access to the following functions:
 - 1. Live view window size
 - 2. Resolution setting
 - 3. Image (snapshot) capture
 - 4. Manual recording to SD or NAS
 - 5. Audio/microphone control
 - 6. Activate alarm output
 - 7. Access Playback and Setup menus
- C. The web viewer shall provide a playback screen which provides access to the following functions:
 - 1. Search date and time range
 - 2. Search event type
 - 3. Play an event video
 - 4. Set resolution
 - 5. Play audio if present
 - 6. Generate a backup copy of saved video data
- D. The web viewer shall provide a setup screen which provides access to the following configuration settings and functions in the camera:
 - 1. Digital video profile to include compression type, maximum or target bit rate, frame rate, multicast parameters, crop encoding area
 - 2. User profile to include password, access level, authentication
 - 3. Date and time
 - 4. Network settings and IP version
 - a. DDNS
 - b. SSL, including certificate management
 - c. 802.1x authentication
 - d. Quality of Service settings
 - e. SNMP to include version selection and settings
 - f. Auto configuration
 - 5. Video setup to include flip and mirror mode, analog output enable, video type, privacy zone
 - 6. Audio setup to include source, audio codec type, gain, and bit rate
 - 7. Camera settings to include image preset, sensor frame capture, dynamic range, white balance, back light, exposure, day/night operation, on-screen display, sharpness, contrast, color level, defog, enhanced quality region of interest (Smart Codec), focus.

8. Event detection setup to include notification parameters, recording rules, alarm input and output, time schedule, tamper protection, motion detection, video analytics, face detection, audio analytic threshold, event triggers
 9. System function to include reboot, upgrade, check system and event logs, application (SDK) management
 10. View profile information
- E. Minimum client hardware requirements
1. Processor: Intel Core 2 Duo 2.6GHz or higher
 2. RAM: 2 GB
 3. Acceptable Operating Systems: Windows XP / VISTA / 7 / 8, MAC OS X 10.7~10.8
 4. Display: 1280X1024 pixels or higher (32 bit color)
 5. Acceptable browsers: Microsoft Internet Explorer, Mozilla Firefox, Google Chrome, Apple Safari

2.04 DETAILED SPECIFICATIONS

A. Video

1. Imager

- a. Sensor: 1/3" 1.3M CMOS
 - 1.) pixels per sensor: 1312 (H) x 1069 (V) total; 1305 (H) x 1049 (V) effective
 - 2.) scanning: progressive
- b. Minimum illumination
 - 1.) Color mode: 0.1Lux (1/30sec, F1.6, 50IRE, AGC high),
0.005Lux (2sec, F1.6, 50IRE, AGC high)
0.05Lux (1/30sec, F1.6, 30IRE)
0.0025Lux (2sec, F1.6, 30IRE)
 - 2.) Black & white mode: 0.01Lux (1/30sec, F1.6, 50IRE, AGC high),
0.0005Lux (2sec, F1.6, 50IRE, AGC high)
0.005Lux (1/30sec, F1.6, 30IRE),
0.00025Lux (2sec, F1.6, 30IRE)
- c. Signal: Noise ratio: 50 dB
- d. The following features with control settings shall be available:
 - 1.) Backlight compensation (BLC): On/Off
 - 2.) Camera title: On/Off, Up to 45 characters
 - 3.) Contrast enhancement: On/Off
 - 4.) Day/night setting: Auto (ICR), Color, B/W
 - 5.) Digital Noise Reduction (DNR): On/Off
 - 6.) Digital image stabilization: On/Off
 - 7.) Defog: Off/ Manual/Auto
 - a.) level: 10 step adjustment
 - 8.) Electronic shutter speed: 2 - 1/12,000 sec.
 - a.) settings: min, max, anti-flicker
 - 9.) Image flip: On/Off

- 10.) Image mirror: On/Off
- 11.) Automatic gain control: 3 levels or Off
- 12.) Motion detection
 - a.) 4 zones with 4 sided polygon
 - b.) selectable for On/Off
- 13.) Privacy masking
 - a.) 32 zones with 4 sided polygon
 - b.) selectable for On/Off
- e. Lens: 4.44 – 102.1 mm
 - 1.) Optical zoom ratio 23x
 - 2.) Angle of view: H : 56.8°(Wide) – 2.8°(Tele) / V : 46.3°(Wide) – 2.24°(Tele)
 - 3.) Minimum Object Distance:
 - a.) Wide: 1.5 m (4.92 ft.)
 - b.) Tele: 2 m (6.56 ft.)
 - 4.) Focus control: Auto / Manual / One Push
 - 5.) Maximum aperture ratio: F1.6 (Wide), F3.63 (Tele)
 - 6.) Lens Type: DC auto Iris
 - 7.) Mount Type: Board-in Type
- f. Manual positional settings:
 - a.) pan: 0 – 360°
 - b.) tilt: 0 – 210° (-15° ~ 195°)
 - c.) rotation 0 – 360°
- g. Analog output: 1.0 V p-p / 75Ω composite, 720 x 480(NTSC), 720 x 576(PAL)
 - 1.) connector type: DIP (supplied)
- 2. Video Streams
 - a. The 1.3 MP camera shall have 10 video profiles, each of which may have the following properties:
 - 1.) Encoding type:
 - a.) H.264
 - b.) MJPEG
 - 2.) Resolution: 1280 x 1024, 1280 x 960, 1280 x 720, 1024 x 768, 800 x 600, 800 x 450, 720 x 576, 640 x 480, 640 x 360, 320 x 240, 320 x 180
 - 3.) Bit rate control method:
 - a.) H.264
 - i. compression level control
 - ii. constant bit rate (CBR) or variable bit rate (VBR)
 - b.) MJPEG
 - i. quality level control
 - ii. variable bit rate (VBR)
 - 4.) Maximum frame rate:

- a.) H.264: 30 fps at all resolutions
- b.) MJPEG:
 - i. 30fps @ 800 x 600, 800 x 450, 720 x 576, 640 x 480, 640 x 360, 320 x 240, 320 x 180
 - ii. 15fps @ 1280 x 1024, 1280 x 960, 1280 x 720, 1024 x 768
- 3. Number of multi-streaming profiles: 10 maximum
- 4. Simultaneous users (total): 10 maximum (unicast)
- 5. Storage and Recording
 - a. The 1.3 MP camera shall have onboard SD card storage.
 - 1.) Card type: Micro SD/SDHC/SDXC
 - 2.) Capacity: 4 GB – 64 GB per card
 - 3.) Image content on the card shall have the ability to be downloaded to a selected destination.
- 6. Interoperability - Video streams shall be capable of supporting ONVIF protocol, profiles S.
- 7. Single Images - The 1.3 MP camera shall support jpg file image screenshot and export.

B. Network

- 1. Connectivity: 10/100 Base-T Ethernet via RJ-45 connector
- 2. Protocols supported:
 - a. Transmission Control Protocol (TCP), Internet Protocol (IP) v4 and v6, User Datagram Protocol (UDP)
 - b. Configuration: Dynamic Host Configuration Protocol (DHCP)
 - c. Web services: Hypertext Transfer Protocol (HTTP), Secure HTTP (HTTPS)
 - d. Network services: Address Resolution Protocol (ARP), Bonjour, Domain Name System (DNS), Internet Control Message Protocol (ICMP), Network Time Protocol (NTP), Protocol Independent Multicast-Sparse Mode (PIM-SM), Simple Network Management Protocol (SNMP v1/2c/3 – MIB-2), Universal Plug and Play (UPnP)
 - e. Media: Real-Time Transport Protocol (RTP), Real-Time Control Protocol (RTCP), Real-Time Streaming Protocol (RTSP)
 - f. Multicast: Internet Group Management Protocol (IGMP)
 - g. Notifications: File Transfer Protocol (FTP), Simple Mail Transfer Protocol (SMTP)
 - h. Remote Access: Point-to-Point Protocol over Ethernet (PPPoE)
- 3. DDNS – The 1.3 MP camera shall support DDNS services offered by the Manufacturer and other publicly available service offerings.
- 4. Quality of Service (QoS) – Layer 3 DSCP
- 5. Security features:
 - a. user password protection
 - b. IP address filtering - list of allowed or blocked IP addresses
 - c. HTTPS(SSL) login authentication
 - d. HTTPS(SSL) secured communications
 - e. Digest login authentication
 - f. User access log
 - g. 802.1x authentication

6. Discovery - Manufacturer shall offer a discovery program to identify all devices of his manufacture on the network.

C. Audio

1. Direction: bi-directional
2. Levels:
 - a. In: selectable (Mic in / Line in)
 - 1.) supply voltage: 2.5V DC (4mA)
 - 2.) input impedance: 2K ohm
 - b. Out:
 - 1.) Max output level: 1 Vrms
 - 2.) line out: (3.5mm mono jack)
3. Compression:
 - a. G.711 u-law/G.726 selectable
 - 1.) G.726 (ADPCM) 8KHz, G.711 8KHz
 - 2.) G.726: 16Kbps, 24Kbps, 32Kbps, 40Kbps

D. Electrical

1. Power
 - a. Sources
 - 1.) 24 VAC +/- 10%
 - 2.) PoE+: IEEE 802.3af, Class 4
 - b. Power Consumption: Max. 20W
 - c. Ethernet: RJ-45 connector

E. Mechanical And Environmental

1. Material:
 - a. Housing: Plastic + Metal
2. Dimensions (W x H): 5.98 in. x 8.58 in. (152.0 mm x 218.0 mm)
3. Temperature:
 - a. Operating: -10°C ~ +55°C (+14°F ~ +131°F)
 - b. Storage: -30°C ~ +60°C (-22°F ~ +140°F)
4. Humidity: 0 - 90%, non-condensing
5. Environmental Rating:
 - a. Ingress Protection: N/A
 - b. Mechanical (Vandal) Protection: IK10 (with SHP-3701H)

END OF SECTION

PART 3 EXECUTION**3.01 INSTALLERS**

- A. Contractor personnel shall comply with all applicable state and local licensing requirements.

3.02 PREPARATION

- A. The network design and configuration shall be verified for compatibility and performance with the camera(s).
- B. Network configuration shall be tested and qualified by the Contractor prior to camera installation.
- C. All firmware found in products shall be the latest and most up-to-date provided by the manufacturer, or of a version as specified by the provider of the Video Management Application (VMA) or Network Video Recorder (NVR).
- D. All equipment requiring users to log on using a password shall be configured with user/site-specific password/passwords. No system/product default passwords shall be allowed.

3.03 INSTALLATION

- A. The Contractor shall carefully follow instructions in documentation provided by the manufacturer to insure all steps have been taken to provide a reliable, easy-to-operate system.
- B. All equipment shall be tested and configured in accordance with instructions provided by the manufacturer prior to installation.
- C. Before permanent installation of the system, the Contractor shall test the system in conditions simulating the final installed environment.

3.04 STORAGE

- A. The 1.3 MP camera hardware shall be stored in an environment where temperature and humidity are in the range specified by the Manufacturer.

END OF SECTION