

TEST REPORT

1. **Report Number** KR16-YYP0114
2. **Applicant**
 - Name Hanwha Techwin Co.,Ltd
 - Address 1204, Changwon-daero, Seongsan-gu, Changwon-si, Gyeongsangnam-do, Korea
 - Date of Receipt October 14, 2016
3. **Manufacturer**
 - Name Hanwha Techwin Co.,Ltd
 - Address 1204, Changwon-daero, Seongsan-gu, Changwon-si, Gyeongsangnam-do, Korea
4. **Use of Report** For Quality management
5. **Test item description**
 - Product Name Network Camera
 - Model Name PNM-9020V*(*N:NTSC/P:PAL)
6. **Test method used** IEC 62262: 2002 (IK 10)
7. **Date of Test** October 18, 2016
8. **Environment**
 - Temperature (15~35) °C
 - Relative Humidity (25~75) % R.H
 - Air pressure (86~106) kPa
9. **Test Results** See of the test result

※ This test results apply only to the test sample supplied by applicant and do not guarantee the whole product quality. This test report shall not be reproduced except in full, without the written approval by the KCTL Inc.

Affirmation	Tested by	Technical Manager
	Name : Kyung Hoon, Ahn (Signature)	Name : Do Hong, Choi (Signature)

October. 19. 2016

KCTL INC.

— INDEX —

1. Test Laboratory	3
1.1 General	3
1.2 Certificate of Designated Testing Laboratory	3
2. Test equipment	3
2.1 Specitication.....	3
2.2 Product photograph.....	4
3. Test Method and Result	5
3.1 IK10 Impacts Test.....	5

1. Test Laboratory

1.1 General

Name of Test Laboratory	KCTL INC.
Address	52-20, Sinjeong-ro 41 beon-gil, Giheung-gu, Yongin-si, Gyeonggi-do 446-599, Korea
TEL	82 31-326-6700
FAX	82 505-299-8311
Home page	www.kctl.co.kr

1.2 Certificate of Designated Testing Laboratory

Mark.	Registration No.
NRRA	KR0040
KOLAS	No. KT231
IEC(CB-Scheme)	TL512
TUV-SUD	CARAT 15 08 93040 001
VCCI Council	R-3327, C-3706, T-1849, G-198
DSP Research, Inc.	G039
FCC	Test Firm Registration No. 687132
INDUSTRY CANADA	Company Address Code: 8035A

2. Test equipment


2.1 Specification

Division	Specification
Product Name	Network Camera
Model Name	PNM-9020V*(N:NTSC/P:PAL)

2.2 Product Photograph



[Front]



[Rear]

3. Test Method and Result

3.1 IK10 Impacts Test

3.1.1 Test Equipment

Instrument description	Model	Manufacturer	Serial number	Due Cal
20J IMPACT ELEMENT	N/A	CERTIS	None	2016-12-05
Measuring Tape	3.5 m	Komelon	None	2018-07-07
Weighting Scale	DB-60H	CAS	IY1142	2017-02-28
Pendulum Hammer	N/A	N/A	None	2017-07-01

3.1.2 Reference Documents

IEC 62262 and IEC 60068-2-75

Degrees of protection provided by enclosure for electrical equipment against external mechanical impacts (IK code)

3.1.3 Test Performed

Degree of protection provided by enclosure for external impacts IK10

3.1.4 Test Conditions

According to standard IEC 62262 and IEC 60068-2-75

The verification of IK10 has been done positioning the enclosure on a rigid support.

5 impacts have been applied on each surface in sight with the enclosure.

For the test used Pendulum Hammer

IK10 (Characteristics of impact test):

Energy: 20 Joule

Mass: 5.0 kg

High Δh : 400 mm


3.1.5 Test Criteria

Visual inspection after impact test.

Check if breakage, Crack, separation occur.

3.1.5 Drop Zones:

The areas that were focused upon for this impact test are as follows:




3.1.6 Test Results

Drop Zone: Window		
Drop #	Orientation	Results
Drop 1	Vertical drop onto center of Window.	No abnormal was found ※ Refer to 3.1.8
Drop 2	Normal to surface of side Window.	
Drop 3	Normal to surface of side Window, about 90° circumferentially from previous drop.	
Drop 4	Normal to surface of side Window, about 90° circumferentially from previous drop.	
Drop 5	Normal to surface of side Window, about 90° circumferentially from previous drop.	


Drop Zone: Enclosure		
Drop #	Orientation	Results
Drop 1	Normal to surface of enclosure.	No abnormal was found ※ Refer to 3.1.8
Drop 2	Normal to surface of enclosure, about 90° circumferentially from previous drop.	
Drop 3	Normal to surface of enclosure, about 90° circumferentially from previous drop.	
Drop 4	Normal to surface of enclosure, about 90° circumferentially from previous drop.	
Drop 5	Normal to surface of enclosure, about 90° circumferentially from previous drop.	

※ Allow extent of damage: Scuff

3.1.7 TEST Photograph




[During the test_Window]




[During the test_Enclosure]

3.1.8 Test Result Photograph



[Test result_Window]



[Test result_Enclosure]