

## **SNP-5430 1.3 MEGAPIXEL HD 43X NETWORK PTZ DOME CAMERA**

### **TECHNICAL SPECIFICATIONS**

### **SECURITY SYSTEM**

#### **DIVISION – 28 ELECTRONIC SAFETY AND SECURITY**

#### **LEVEL 1 \_28 20 00 ELECTRONIC SURVEILLANCE**

#### **LEVEL 2 \_28 23 00 VIDEO SURVEILLANCE**

#### **LEVEL 3 \_28 23 29 VIDEO SURVEILLANCE REMOTE DEVICES AND SENSORS**

### **PART 2 – PRODUCTS**

#### **2.01 GENERAL**

- A. All equipment and materials used shall be standard components that are regularly manufactured and used in the manufacturer's system.
- B. All systems and components shall have been thoroughly tested and proven in actual use.
- C. All systems and components shall be provided with the availability of a toll-free (U.S. and Canada), 24-hour technical assistance program (TAP) from the manufacturer. The TAP shall allow for immediate technical assistance for either the dealer/installer or the end user at no charge for as long as the product is installed.

#### **2.02 SNP-5430H 1.3MEGAPIXEL HD 43X NETWORK PTZ DOME CAMERA**

- A. These cameras shall support multi-streaming technologies, transferring real-time high resolution images at 60 fps with video compression in H.264 and MJPEG codec.
- B. The camera shall provide 3.5~150.5mm (43x) optical zoom with 16x digital zoom. It shall support PoE plus, SD memory, and bi-directional audio.
- C. All operation and configuration menus shall be provided English, French, German, Spanish, Italian, Chinese, Korean, Russian, Japanese, Swedish, Danish, Portuguese, Turkish, Polish, Czech, Rumanian, Serbian, Dutch, Croatian, Hungarian, Greek, Finnish, Norwegian

#### **2.03 ELECTRICAL SPECIFICATIONS**

- A. Input Voltage / Current 24V AC+-10%, PoE+ (IEEE802.3af class3)
- B. Power Consumption, Max. 24W 24W (Heater off),  
Max. 65W (Heater on, 24V AC)

#### **2.04 CAMERA**

- A. Imaging Device 1/4" 1.3M CMOS
- B. Total Pixels (horizontal x vertical) 1,392,(H) x 1,076(V) 1.49M pixels
- C. Effective Pixels (horizontal x vertical) 1,368(H) x 1,049(V), 1.43M pixels
- D. Scanning System Progressive
- E. Min. Illumination
  - 1. Color 0.5Lux (F1.4, 50IRE), 0.3Lux (F1.4, 30IRE),
  - 2. B/W 0.01Lux (F1.4, 50IRE), 0.006Lux (F1.4, 30IRE)
- F. S / N ratio 50dB
- G. Video Output CVBS:1.0 Vp-p
  - 1. NTSC 704x480, for installation
  - 2. PAL 704x576, for installation

#### **2.05 LENS**

- A. Focal Length (Zoom Ratio) 3.5 ~ 150.5mm (Optical 43x)
- B. Angular Field of View
  - H : 53.92°(Wide) ~ 1.396°(Tele) /
  - V : 44.08°(Wide) ~ 1.12°(Tele)
- C. Max. Aperture Ratio F1.4(Wide) / F4.9(Tele)
- D. Min. Object Distance Wide : 1.5m (4.92ft), Tele : 2m (6.56ft)

E. Focus control	Auto / Manual / One push
B. Lens Type	DC auto iris
C. Mount Type	Board-in type

## 2.06 OPERATIONAL SPECIFICATION

A. Camera Title	On, Off (displays up to 45 characters)
B. Day and Night	Auto (ICR), Color, B/W
C. Backlight Compensation	BLC, HLC, Off, WDR
D. Wide Dynamic Range	120dB
E. Contrast Enhancement	SSDR (Samsung Super Dynamic Range) (Off / On)
F. Digital Noise Reduction	SSNR/III (2D+3D noise filter) (Off / On)
G. Digital Image Stabilization	Off, On
H. Defog	Off, Auto, Manual
I. Motion Detection	On, Off (4ea rectangle zone)
J. Privacy Masking	On, Off (32 zones of rectangle zone)
K. Gain Control	Off, Low, Middle, High
L. White Balance	ATW / AWC / Manual / Indoor / Outdoor / Mercury / Sodium
M. Electronic Shutter Speed	Minimum / Maximum / Anti flicker (2 ~ 1/12,000sec
N. Digital Zoom	16x
O. Flip/Mirror	Off, On
P. Intelligent Video Analytics	Tampering, Virtual line, Enter / Exit, Appear / Disappear, Audio detection, Face detection
Q. Alarm I/O	Input 4ea / Output 2ea(relay).
R. Remote control Interface	RS-485
S. RS-485 Protocol	Samsung-T/E, Pelco-P/D, Sungjin, Panasonic, Honeywell, AD, Vicon, Bosch, GE
T. Alarm Triggers	Motion detection, Tampering, Audio detection, Face detection, Video analytics, Alarm input, Network disconnection
U. Alarm Events	File upload via FTP and E-mail, Notification via E-mail, TCP and HTTP, local storage (SD/SDHC/SDXC) recording at network disconnected & event (Alarm triggers), External output

## 2.07 NETWORK

A. Ethernet	RJ-45 (10/100Base-T)
B. Video Compression	H.264(MPEG-4 part 10 / AVC), MJPEG
C. Resolution	1280 x 1024, 1280 x 720, 1024 x 768, 800 x 600, 640 x 480, 320 x 240
D. Max Frame rate	H.264 : Max. 60fps at all resolutions MJPEG : 1280 x 1024, 1280 x 720, 1024 x 768 : Max. 15fps 800 x 600, 640 x 480, 320 x 240 : Max. 30fps
E. Video Quality Adjustment	Compression level, Target bit rate level control Quality level control
1. H.264	
2. MJPEG	
F. Bitrate Control Method	VBR or CBR
1. H.264	VBR
2. MJPEG	Multiple, up to 10 profiles
G. Streaming	Selectable (Mic in / Line in), Supply voltage : 2.5V DC (4mA), Input impedance : approx. 2K Ohm
H. Audio In	Line out (3.5mm mono jack), Max output level : 1 Vrms
I. Audio out	

J. Audio Compression Format	G.711 u-law/G.726 selectable, G.726 (ADPCM) 8KHz, G.711 8KHz, G.726 : 16Kbps, 24Kbps, 32Kbps, 40Kbps
K. Audio Communication	Bi-directional audio
L. IP	IPv4, IPv6
M. Protocol	TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTSP, NTP, HTTP, HTTPS, SSL, DHCP, PPPoE FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS, PIM-SM, UPnP, Bonjour
N. Security	HTTPS(SSL) login authentication, Digest login authentication, IP address filtering, User access log, 802.1x authentication
O. Streaming Method	Unicast, Multicast
P. Max. User Access	15 users at Unicast
Q. Memory Slot	SD/SDHC/SDXC (SNP-6320 : micro SD type, SNP-6320H : SD type) - Motion Images recorded in the SD/SDHC/SDXC memory card can be downloaded. NAS (Network Attached Storage)
R. Application Programming Interface	ONVIF profile S, SUNAPI 2.0, SVNP 1.2
S. Webpage Language	English, French, German, Spanish, Italian, Chinese, Korean, Russian, Japanese, Swedish, Danish, Portuguese, Turkish, Polish, Czech, Rumanian, Serbian, Dutch, Croatian, Hungarian, Greek, Finnish, Norwegian
T. Web Viewer	
1. Supported OS	Windows XP / VISTA / 7 / 8 or higher, MAC OS X 10.7
2. Supported Browser	Microsoft Internet Explorer (Ver. 8 ~ 11), Mozilla Firefox (Ver. 9 ~ 19), Google Chrome (Ver. 15 ~ 25), Apple Safari (Ver. 6.0.2 (Mac OS X 10.8, 10.7 only), 5.1.7) * Mac OS X only
U. Central Management Software	Smart Viewer, SSM
<b>2.08 ENVIRONMENTAL SPECIFICATIONS</b>	
A. Operating Temperature / Humidity	-10°C ~ +55°C (-22°F ~ +131°F) / Less than 90% RH
B. Storage Temperature / Humidity	-30°C ~ +60°C (-22°F ~ +140°F) / Less than 90% RH
C. Ingress Protection	N/A
D. Vandal Resistance	IK10(With SHP-3701H)
<b>2.09 PHYSICAL SPECIFICATIONS</b>	
A. Dimension	Ø152 x 218.0mm (Ø5.98" X 8.58")
B. Weight	2.2kg (4.85 lb)
C. Color	Ivory
D. Material	Plastic + Metal
<b>2.10 CERTIFICATIONS</b>	
A. UL Listed	
B. CE mark	
C. FCC mark	
<b>2.11 WARRANTY</b>	
A. 3 years	